

## ADVANCED ILLUMINATION AL295 MICROBRITE BAR LIGHT

Compact Area Lighting

AL295-150-530C5

Ai MicroBrite™ Bar Light, 150mm, Green, pulsar



- High-performance compact line light
- Available in 76 mm (3 inch) increments up to 457 mm (18 inches)

### PRODUCT DESCRIPTION

The AL295 is part of the Microbrite family of high performance, compact machine vision lights. Outperforming the competition with a high intensity output of 73 kLux at a working distance of 100mm. The AL295 is available in expandable sizes in 3" increments up to 18".

Power options include:

- C1 connector - for use with DCS series controllers
- C5 connector - for use with Pulsar 320 strobe controller
- Continuous in-line controller - powered by 24V power supply
- Combination strobe/continuous in-line controller - powered by 24V power supply
- Default-OFF strobe/continuous in-line controller - powered by 24V power supply
- Flying/tinned leads - powered by 24V power supply

Other Wavelength options:

- UV - 365, 375, 385, 395, 405
- Royal blue - 455
- Blue - 470
- Cyan - 505
- Green - 530
- Amber - 590
- Red orange - 625
- Red - 660
- Infrared - 730, 850, 940
- White - WHI

For enquiries or quotes for wavelength and power options not listed here please [contact us](#).

## TECHNICAL DATA

### TECHNICAL DATA

Wavelength	530
Colour	Green
Length	166 mm

Width	20 mm
Connector/controller	C5 connector
Standard cable length	Up to 2 meters
Photobiological risk factor IEC 6247	Group 1 (low risk)
Operating temperature	0 - 60°C
Approvals	IEC 62471, CE, RoHS
IP class	IP50
Weight	68.9 g

