

OEM Automatic Ltd


Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

ADVANCED ILLUMINATION BL 138 SERIES BACK LIGHTS

Expandable High Power Linear Backlights

BL13806-53024 Ai High Power Linear Backlight, 6", Green, 24V A DVANCED ILLUMINATION

- 510,000 lux perfect for line-scanning applications
- Available 6" (152.4mm) increments from 6" (152.4mm) to 96" (2438.4mm) with the exception of a 3" (76.2mm)model
- Intensity control of entire light via 0 10v input



PRODUCT DESCRIPTION

The BL138 is a high intensity linear backlight offering 510 kLux output, making this perfect for back-lit, line scanning applications. Available from 6" length up to 96" in increments of 6". A 3" (75mm) length option is also available. Available intensity control provides illuminance adjustability for every 6" increment via a 0 – 10v input.

Power options include:

- C1 connector for use with DCS series controllers
- C5 connector for use with Pulsar 320 strobe controller
- Continuous in-line controller powered by 24V power supply
- Flying/tinned leads powered by 24V power supply

For enquiries or quotes for sizes and power options not listed here please contact us.

TECHNICAL DATA

TECHNICAL DATA

Wavelength	530
Colour	Green
Length	152 mm
Width	90.8 mm
Connector/controller	flying/tinned leads
Standard cable length	Up to 2 meters
Photobiological risk factor IEC 6247	Group 1 (low risk)
Operating temperature	0°C - 60°C
Approvals	IEC 62471, CE, RoHS
IP class	IP50

