

ADVANCED ILLUMINATION BL 138 SERIES BACK LIGHTS

Expandable High Power Linear Backlights

BL13806-85024

Ai High Power Linear Backlight, 6", IR, 24V

- 510,000 lux - perfect for line-scanning applications
- Available 6" (152.4mm) increments from 6" (152.4mm) to 96" (2438.4mm) with the exception of a 3" (76.2mm) model
- Intensity control of entire light via 0 - 10v input



PRODUCT DESCRIPTION

The BL138 is a high intensity linear backlight offering 510 kLux output, making this perfect for back-lit, line scanning applications.

Available from 6" length up to 96" in increments of 6". A 3" (75mm) length option is also available. Available intensity control provides illuminance adjustability for every 6" increment via a 0 – 10v input.

Power options include:

- C1 connector - for use with DCS series controllers
- C5 connector - for use with Pulsar 320 strobe controller
- Continuous in-line controller - powered by 24V power supply
- Flying/tinned leads - powered by 24V power supply

For enquiries or quotes for sizes and power options not listed here please [contact us](#).


TECHNICAL DATA

TECHNICAL DATA

Wavelength	850
Colour	Infrared
Length	152 mm
Width	90.8 mm
Connector/controller	flying/tinned leads
Standard cable length	Up to 2 meters
Photobiological risk factor IEC 6247	Exempt
Operating temperature	0°C - 60°C
Approvals	IEC 62471, CE, RoHS
IP class	IP50

Diagram illustrating the dimensions and mounting options for the MMS-1000:

- Top width: 3.1 (±.12)
- Bottom width: 3.13 (±.12)
- Height: 90.8 (±.58)
- Mounting channel height: 0.88 (±.03)
- Label: SEE CHART
- Label: MMS NUT CHANNEL FOR MOUNTING (HARDWARE INCLUDED)
- Label: OPTIONAL IC HOLE LOCATION



Technical drawing of the 10' x 10' x 10' storage bin. The drawing shows the bin's profile with dimensions: 3.1 (0.12) for the top rail, 90.8 (3.58) for the main body, and 0.88 (0.03) for the base. A label 'SEE CHART' is at the top. A label 'M6 NUT CHANNEL FOR MOUNTING (PAREDRIVE INCLUDED)' points to a feature on the side. A label 'OPTIONAL IC HOLE LOCATION' points to a feature on the end panel.

