


## PTKS PUSH IN TRANSFORMER TERMINALS

### PTKS

27088.6

PTKS 4/SI 6.3x32 Grey, 4mm<sup>2</sup> Push-in fuse terminal  
(6.3x32mm fuses)

- Push-In technology
- Protective covers
- Cross Connectable
- Clip together



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### GENERAL DATA

Colour	Grey
Rated cross section	4 mm <sup>2</sup>
Rated current	10 A
Rated voltage	250 V
Rated impulse voltage	6 kV
Overvoltage category	III
Contamination degree	3

#### DIMENSIONS

Length	32.5 mm
Width	12.5 mm
Height	49.4 mm

#### CONNECTION DATA

Connections	1
Cross connect channels	1

Cross section single wire from	0.5 mm <sup>2</sup>
Cross section single wire to	6 mm <sup>2</sup>
Cross section stranded wire from	0.5 mm <sup>2</sup>
Cross section stranded wire to	4 mm <sup>2</sup>
Cross section stranded with ferrule from	0.5 mm <sup>2</sup>
Cross section stranded with ferrule to	4 mm <sup>2</sup>
Rated wire cross section from (AWG)	21
Rated wire cross section to (AWG)	10
Stripping length	12 mm

## MATERIALS

Material	Polyamide 6.6
Insulation material	Polyamide 6.6
Flammability class	V-0
Operating temperature from	-40 °C
Operating temperature to	120 °C

## APPROVALS

KEMA KEUR test standard	EN 60947-7-1:2009
-------------------------	-------------------

## ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	11.76 g
Pack size	50

