

## IBOCO NARROW SLOT TRUNKING

T1-EF100X80-G  
100W x 80H Trunking NS 16m/Pk B01130

- PVC Narrow Slot Trunking
- From 40mm to 100mm height, 25mm to 100mm width
- 2m lengths
- EN 50085-2-3, UL94 V0



### PRODUCT DESCRIPTION

Iboco Narrow Slot Trunking, T1-E series, is a high-performance PVC cable trunking system designed for efficient and reliable cable management in industrial and commercial electrical installations. Manufactured from self-extinguishing PVC rated to UL94 V0, the trunking provides excellent flame resistance and long-term durability. It is fully compliant with EN 50085-2-3, with base holes produced according to EN 50085.

Engineered with narrow slot sidewalls, the T1-E series supports precise cable routing while maintaining strong wire retention, making it suitable for high-density wiring environments. The product includes two predetermined scorelines that allow either partial finger removal or complete sidewall removal for flexible wiring options.

Available in a wide range of sizes, with cross-sectional areas from 820 mm<sup>2</sup> to 6300 mm<sup>2</sup>, the T1-E series offers configurations such as 25×40, 40×40, 60×40, 80×40, and 100×40.

Typical applications include electrical control panels, automation systems, machine building, communication cabinets, HVAC control panels, and any environment requiring structured, secure, and space-efficient cable trunking. With excellent thermal resistance from -45°C to +60°C, narrow slot, and strong certification credentials, Iboco T1-E Narrow Slot Trunking delivers dependable performance for modern wiring installations.

### TECHNICAL DATA

#### GENERAL DATA

Width	100 mm
Height	80 mm
Colour	Grey RAL 7030

#### DIMENSIONS

Width of slot	4 mm
Length	2000 mm

#### MATERIALS

Material	PVC-U
----------	-------

<b>Flammability class</b>	UL94-V0
<b>Halogen-free</b>	No
<b>Operating temperature from</b>	-15 °C
<b>Operating temperature to</b>	60 °C

## APPROVALS

<b>Approvals</b>	CE, UL, CSA, Rina
------------------	-------------------

## ADDITIONAL DATA

<b>Tariff code</b>	39259020
<b>Country of origin</b>	IT
<b>Type</b>	Narrow Slot
<b>Width of Finger</b>	6 mm
<b>Pack size</b>	16 m
<b>Weight</b>	1024g/m