

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

## **DOGA - 168 SERIES**

DC motor only, planetary option

168.4105.30.04 Motor 24 V dc, 0.5 Nm, 1900 rpm, 7 A, shaft E8

- 12-24Vdc
- Up to 0.75 Nm
- Up to 3000 rpm
- 79mm diameter
- · High starting torque



## PRODUCT DESCRIPTION

The DOGA 168 series is a range of 79mm diameter permanent magnet DC motors that are developed for a compact, low noise and cost-effective solution to suit many industrial applications. IP40 is standard, with an EMC filter option.

VOLTAGE: 12 / 24Vdc supply - ideally suited to battery powered and mobile applications.

TORQUE: >0.75Nm nominal, >3.0Nm starting – a good choice for applications requiring high start-up power.

SPEED: 750 - 3000rpm options.

For modest quantities DOGA can offer product customisation to better suit the individual needs of the customer and application. Adaptations can include changes to the output shaft, supply voltage, cabling/connectors and motor windings.

Typical applications include:

Agriculture **Building access** Care aid Medical Office equipment Marine General industrial automation

## **TECHNICAL DATA**

Current max	32 A
EMC filter	No
IP class	IP40
Max. torque	3
Nominal current	7 A
Nominal speed	1900 rpm
Nominal torque	0.5
Shaft diameter	8 mm



Supply voltage 24 V DC

Weight 2.6 kg









