

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

## **MINIMOTOR - MCC WORM GEAR MOTOR**

MCC12MP3B3-373 12V dc 373rpm 0.6Nm B3 mount

- 12 or 24VDC
- 37 to 150W delivered power
- Up to 9Nm rated torque
- B3 foot or B5 flange mounting
- IP65 as standard



## PRODUCT DESCRIPTION

High quality, designed from the ground up to IP65 rated compact gear motor.

Physically smaller than the majority of similar powered gear motors due to the use of high quality components in precision manufacturing.

Ideally suited to many applications, including label and packaging machines, conveyors, pharmaceutical and medical machinery

MP MOTOR: Direct current with permanent magnets. Totally enclosed, with external ventilation. Class F winding. 12 or 24 Vdc power supply. Absorbed power 60 W. IP 65 protection according to CEI EN 60529.

MP3N-MP4N MOTOR: Direct current with permanent magnets. Totally enclosed without external ventilation. Class F insulation. 12 or 24 Vdc power supply. Absorbed power 230 W. IP65 protection according to CEI EN 60529.

GEAR UNIT: Die-cast aluminium casing. Centre distance 26 mm. CARO bronze ring, 120÷160 HB hardness. Hardened steel screw with ground thread rotating on ball and roller bearings. Lubrication with special long life oil. Sealing rings made in special rubber for high temperatures. 9 gear ratios (i) available, from 7.5 to 80. Rated torque 9 Nm. Version B3 or B5. B5/S left version - B5/D right version

Please click here for 2D and 3D drawings

## **TECHNICAL DATA**

| Input voltage dc | 12V     |
|------------------|---------|
| IP class         | IP65    |
| Nominal speed    | 373 rpm |
| Nominal torque   | 0.6     |
| Output power     | 37 W    |
| Rated current    | 5A      |
| Ratio            | 7.5:1   |



