OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

IDEM - STAINLESS STEEL BELT ALIGNMENT SWITCH

501001
Belt Switch SS 35mm Roller Short M20 2NC 2NO



- Two-step operation
- 3 types of lever rollers
- Adjustable angle of operation
- 2 independent contact blocks 1NO + 1NC


PRODUCT DESCRIPTION

The IDEM sensor range complements a wide range of cable switches used for emergency stop along conveyors. They are mounted along the conveyor belt and indicate the crookedness of the conveyor belt. We offer standard models (aluminum alloy) and made of stainless steel. Sensors are available with different roll diameters, thus ensuring a long service life even under severe operating conditions.

TECHNICAL DATA

Approvals	IEC 60947-5-1
ATEX approved	No
Conduit entry	4 x M20
Contacts	2NC 2NO
Housing material	Stainless steel
Integrated LED indication	No
IP class	IP67
Material contacts	Silver
Mounting	4 x M5
Operating temperature	-25°C...+80°C
Operational rating	AC15 A300 240V. 3A. / 120V. 6A. ac, 24V. 2,5A dc
Rated insulation voltage	500V
Thermal current (Ith)	10 A
Utilisation category	AC15

Withstand voltage	2500V



Belt Switch - 35mm Short Roller

All Dimensions in mm