

## IDEM - STAINLESS STEEL TAPE CONVERGENCE SENSORS

501005

Belt Switch SS 35mm Roller Long M20 2NC 2NO



- Two-step operation
- 3 types of lever rollers
- Adjustable angle of operation
- 2 independent contact blocks 1NO + 1NC




### PRODUCT DESCRIPTION

The IDEM sensor range complements a wide range of cable switches used for emergency stop along conveyors. They are mounted along the conveyor belt and indicate the crookedness of the conveyor belt. We offer standard models (aluminum alloy) and made of stainless steel. Sensors are available with different roll diameters, thus ensuring a long service life even under severe operating conditions.

### TECHNICAL DATA

Approvals	IEC 60947-5-1
ATEX approved	No
Conduit entry	4 x M20
Contacts	2NC 2NO
Housing material	Stainless steel
Integrated LED indication	No
IP class	IP67
Material contacts	Silver
Mounting	4 x M5
Operating temperature	-25°C...+80°C

<b>Operational rating</b>	AC15 A300 240V. 3A. / 120V. 6A. ac, 24V. 2,5A dc
<b>Rated insulation voltage</b>	500V
<b>Thermal current (Ith)</b>	10 A
<b>Utilisation category</b>	AC15
<b>Withstand voltage</b>	2500V



**Belt Switch - 35mm Long Roller**  
All Dimensions in mm