

## MOLEX - MPM DIN FORM A IP67 MOULDED CABLE CONNECTOR

152P3N5001P

Form A, 2P+Earth, PUR, 5m Length, Integrated Gasket

- Fully overmoulded providing a high level of protection
- With or without LED and transient protection
- Integrated gasket and screw, IP67
- EN175301-803 (DIN43650)-A
- 2 pole or 3 pole + earth



### PRODUCT DESCRIPTION

IP67 rated DIN valve connectors with improved strain relief. Cable retention force increased by up to 20% over internal nut styles. Enlarged Cable range that covers the internal thread connector cable range. Conforms to EN 175301-803.

### TECHNICAL DATA

|                          |  |
|--------------------------|--|
| Cable diameter           | 6,5  |
| Cable length             | 5000 mm                                      |
| Circuit                  | No circuit                                   |
| Colour cable             | Black  |
| Colour LED               | No LED                                       |
| Contact resistance       | ≤15 mΩ                                       |
| Core identification      | Colour Coded                                 |
| Current max              | 5 A  |
| Halogen-free             | No   |
| Housing Colour           | Black  |
| IP class                 | IP67   |
| LED indicator            | No   |
| Material cable           | PUR  |
| Material packing         | NBR  |
| Number of poles          | 2 + earth                                    |
| Rated wire cross section | 0,75 mm <sup>2</sup>                         |
| Rated voltage            | 250 V  |
| Screw and gasket         | NBR integrated gasket assembled + IP67 screw |

