

MOLEX - MPM DIN FORM A LOW HOUSING / HIGH HOUSING

28300N0S

Form A, 3P+Earth, Ext thread, Silicone Gasket, IP67, Black

- With or without LED and transient protection
- Fibreglass-reinforced housing
- Turnable insert
- EN175301-803 (DIN43650)-A



PRODUCT DESCRIPTION

Standard internal thread DIN valve connector, IP65 rated. Available with different thread style, gaskets and circuitry. Conforms to EN 175301-803.

IP67 rated DIN valve connectors with improved strain relief. Cable retention force increased by up to 20% over internal nut styles. Enlarged Cable range that covers the PG9 and PG11 internal thread connector cable range. Conforms to EN 175301-803.

TECHNICAL DATA

Cable diameter max	9 mm
Cable diameter min	4 mm
Circuit	No circuit
Colour LED	No LED
Connector	DINA 43650
Cross section max	1.5 mm ²
Current max	16 A
Housing Colour	Black
Housing material	Polyamide
IP class	IP67
LED indicator	No
Manufacturer part no.	1212010030
Material packing	Silicone
Number of poles	3 + earth

Rated voltage	250 V AC/300 V DC
Screw and gasket	Integrated NBR Gasket & IP67 screw
Temperature operational max	90 °C
Temperature operational min	-40 °C

