OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

MOLEX - MPM DIN C INDUSTRIAL / DIN C OVERMOULDED CABLE

392N2N30011C4H
Form Micro, 2P+Earth, H03 PVC, 3m Length, C4, 24V, Yellow



- Fully overmoulded providing a high level of protection
- Quick and simple installation
- With or without LED and transient protection
- 9.4 mm or 8 mm contact distance EN175301-803 (DIN43650-C Industrial/-C)


PRODUCT DESCRIPTION


DIN Valve Connectors with moulded cable, IP65 rated. IP67 version available on request. Conforms to EN 175301-803.

TECHNICAL DATA

TECHNICAL DATA

Number of poles	2 + earth
Cable length	3 m
Material cable	PVC
Circuit	C4: LED & varistor
IP class	IP65
Rated wire cross section	0.5 mm²
Cable diameter	5,4mm
LED indicator	Yes
Connector	DIN C micro 94mm
Temperature operational max	90 °C
Temperature operational min	-40 °C
Current max	3 A
Rated voltage	24 V AC/DC
Screw size	M3x20
Material packing	NBR
Colour LED	Yellow
Manufacturer part no.	1210500177


16
32,8
35
9
19
18
4
18
M 3
1,8
9,4
9,4


V ac-dc