

MOLEX - MPM M8/M12-DIN A / DIN B INDUSTRIAL MOULDED CABLE CONNECTORS

F850B0P12M006

Cordset M12 str. male-DINB LED+VDR 60cm

- Fully overmoulded for better protection
- Quick and simple installation with M8 and M12
- With or without LED and transient protection
- EN175301-803 (DIN43650)-M8 / M12



PRODUCT DESCRIPTION

DIN Valve Connectors with moulded cable, IP65 rated. IP67 version available on request.

TECHNICAL DATA

Cable length	0.6 m
Circuit	C4: LED & varistor
Colour cable	Black
Colour LED	Yellow
Connection - male	M12
Connector	DINB Industry
Contact head 1	DIN
Current max	3 A
IP class	IP65
LED indicator	Yes
Material cable	PUR/PVC
Rated wire cross section	0.5 mm ²
Temperature range fixed use from	-40 °C
Temperature range flexible use from	-15 °C
Temperature range flexible use to	90 °C
Voltage ac/dc max	24 V

3. sor. kabl
A
1 2 3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100

