

## MOLEX - MPM DIN FORM A LOW HOUSING / HIGH HOUSING

C28200N0R  
 Form Industrial, 2P+Earth, Ext Thread, NBR Gask,  
 IP67, Black

- With or without LED and transient protection
- Fibreglass-reinforced housing
- Turnable insert
- EN175301-803 (DIN43650)-A



### PRODUCT DESCRIPTION

Standard internal thread DIN valve connector, IP65 rated. Available with different thread style, gaskets and circuitry. Conforms to EN 175301-803.

IP67 rated DIN valve connectors with improved strain relief. Cable retention force increased by up to 20% over internal nut styles. Enlarged Cable range that covers the PG9 and PG11 internal thread connector cable range. Conforms to EN 175301-803.

### TECHNICAL DATA

Cable diameter max	9 mm
Cable diameter min	4 mm
Circuit	No circuit
Colour LED	No LED
Connector	DINA 43650
Cross section max	1.5 mm <sup>2</sup>
Current max	16 A
Housing Colour	Black
Housing material	Polyamide
IP class	IP67
LED indicator	No
Manufacturer part no.	1212010001
Material packing	NBR
Number of poles	2 + earth

<b>Rated voltage</b>	250 V AC/300 V DC
<b>Screw and gasket</b>	Integrated NBR Gasket & IP67 screw
<b>Temperature operational max</b>	90 °C
<b>Temperature operational min</b>	-40 °C

