

## MOLEX - MPM DIN FORM B INDUSTRIAL / DIN FORM B

C22200N0R

Form Industrial, 2P+Earth, Ext Thread, NBR Gask, IP67, Black

- With or without LED and transient protection
- Fibreglass-reinforced housing
- Turnable insert
- 11 mm or 10 mm connector distance EN175301-803 (DIN43650-B Industrial/-B)



### PRODUCT DESCRIPTION

IP67 rated DIN valve connectors with improved strain relief. Cable retention force increased by up to 20% over internal nut styles. Enlarged Cable range that covers the PG9 and PG11 internal thread connector cable range. Conforms to EN 175301-803.

### TECHNICAL DATA

|                       |                     |
|-----------------------|---------------------|
| Cable diameter max    | 9 mm                |
| Cable diameter min    | 4 mm                |
| Circuit               | No circuit          |
| Colour LED            | No LED              |
| Cross section max     | 1.5 mm <sup>2</sup> |
| Current max           | 16 A                |
| Housing Colour        | Black               |
| Housing material      | Polyamide           |
| IP class              | IP67                |
| LED indicator         | No                  |
| Manufacturer part no. | 1212020001          |
| Material packing      | NBR                 |
| Number of poles       | 2 + earth           |
| Rated voltage         | 250 V AC/300 V DC   |

**Screw and gasket**

Integrated NBR Gasket &amp; IP67 screw

**Temperature operational max**

90 °C

**Temperature operational min**

-40 °C

