

IDEM SAFETY LIMIT SWITCHES LSPS-R (PLASTIC BODY WITH RESET)

173034

LSPS-R long hinge lever M20 '1NC 1NO' snap

- Positive opening safety contacts to IEC60947-5-1
- Lockable head mechanism
- Choice of 8 actuator heads: Linear and Rotary actions.
- Enclosure protection to IP67, suitable for washdown.
- Conduit entries: M20 1/2" NPT or Quick Connect.



PRODUCT DESCRIPTION

IDEM's LSPS-R range of Plastic Body Safety Limit Switches with Manual Reset are designed to be mounted for position sensing of moving applications, e.g. guard doors, conveyors, machine beds, elevators.

Operation

Operation of IDEM Safety Limit Switches is achieved by a sliding actuation of the moving object to cause deflection of the switch plungers, rollers or levers. In addition to the standard LSPS switch they are equipped with a manual reset which needs to be operated after the lock is engaged.

TECHNICAL DATA

Actuator	Long Hinge Lever
Annual usage	8 cycles per hour/24 hours per day/365 days
Approvals	ISO 14119, EN60947-5-1, EN60204-1, ISO 13849-1, EN62061, UL 508
Conduit entry	M20
Contacts	1NC 1NO
Housing material	Glass-filled polyester
Integrated reset button	Yes
IP class	IP67
Mechanical reliability B10d	2.5x10 ⁶ operations at 100mA load
MTTFd	356 years
Operating temperature	-25C +80C
PFHd	3.44 x 10 ⁻⁸

Rated insulation voltage	300Vac
Thermal current (Ith)	10 A