

IDEM DIE-CAST SAFETY LIMIT SWITCHES HLM

174165
HLM Spring Lever EX '2NC 2NO'



- Heavy duty die-cast bodies (red)
- Positive opening NC safety contact
- High mechanical life over 5,000,000 cycles
- Industry standard mounting
- Large choice of actuator heads



PRODUCT DESCRIPTION

IDEM's HLM range of heavy duty Die Cast Safety Limit Switches have been designed to be mounted for position sensing of moving applications e.g. guard doors, conveyors, machine beds and elevators. They are available with an extensive range of actuator heads and can be supplied with either slow break or snap action contacts.

Operation

Operation of IDEM Safety Limit Switches is achieved by a sliding actuation of the moving object to cause deflection of the switch plungers, rollers or levers.

For safety applications it is important that the moving object does not pass completely over the switch actuators so as to either cause damage to the actuator or allow it to return to its original position.

TECHNICAL DATA

Approvals	ISO 13849-1, ISO 14119, EN60204-1, EN62061, EN60947-5-1, UL 508
ATEX approved	Yes
Cable entry	N/A
Conduit entry	3m 8 core Ex
Connection	Cable
Contacts	2NC 2NO

Housing material	Die cast metal
IP class	IP67
Material of body	Metal
Operating temperature	-25C +80C
PFHd	3.44×10^{-8}
Rated insulation voltage	300Vac
Thermal current (Ith)	10 A