

IDEM SAFETY LIMIT SWITCH HLM-SS (STAINLESS STEEL)

175315

HLM-SS Adj Roller Lever EX '2NC 2NO'

- Heavy duty Stainless Steel 316 bodies
- Positive opening NC safety contact
- High mechanical life over 5,000,000 cycles
- Large choice of actuator heads
- IP69K Suitable for washdown



PRODUCT DESCRIPTION

IDEM's HLM range of heavy duty Stainless Steel 316 Limit Switches have been designed to be mounted for position sensing of moving applications e.g. guard doors, conveyors, machine beds and elevators. They are available with an extensive range of actuator heads and can be supplied with either slow break or snap action contacts.

Operation

Operation of IDEM Safety Limit Switches is achieved by a sliding actuation of the moving object to cause deflection of the switch plungers, rollers or levers. For safety applications it is important that the moving object does not pass completely over the switch actuators so as to either cause damage to the actuator or allow it to return to its original position.

TECHNICAL DATA

Actuator	Adjustable Roller Lever
Annual usage	8 cycles per hour/ 24 hours per day/365 days
Approvals	ISO 14119, EN60947-5-1, EN60204-1, ISO 13849-1, EN62061, UL 508
ATEX approved	Yes
Cable entry	N/A
Conductor size	1.5 mm ²
Conduit entry	3M 8 CORE EX
Connection	Cable
Contact voltage/current min	5V, 5mA, DC
Contacts	2NC 2NO
Housing material	Stainless steel 316

IP class	IP67
Material of body	Stainless steel 316
Maximum switching speed	250 mm/s
Mechanical reliability B10d	2.5x10 ⁶ operations at 100mA load
Mounting	M5
MTTFd	356 years
Operating temperature	-25C +80C
PFHd	3.44 x 10 ⁻⁸
PL	up to PLe acc. ISO13849-1
Rated insulation voltage	300 V AC
SIL	up to SIL 3 acc. EN62061
Thermal current (Ith)	10 A
Utilisation category	AC15 A300 240V 3A
Vibration	IEC 68-2-6, 10-55Hz 0,35mm
Withstand voltage	2500 V AC

