

HONSBERG - WO1 SERIES FLOW INDICATOR

Sight Glass

WO1-008GK
15l/min, G1/4, S/S

- G ¼ - 15l/min - G1½ - 220l/min
- Water , Oils
- DN-8-G ¼ - DN40-G1½
- Brass / Stainless Steel
- 16 Bar max

PRODUCT DESCRIPTION**TECHNICAL DATA**

Connection type	G1/4 FEMALE
Flow range max	15 l/min
Flow range min	0 l/min
Material of connection	Stainless steel
Material of glass tube	Borosilicate glass
Material of seals	FKM
Material wipers	FKM
Media	WATER, OILS
Pressure range max	16 bar
Temperature of media from	-20 °C
Temperature of media to	100 °C
Weight	1.5 kg

G	Types	L	SW	X	Weight kg
G 1/4	WO1-008G.	71	36	9	0.3
G 3/8	WO1-010G.				
G 1/2	WO1-015G.	86	46	13	0.6
G 3/4	WO1-020G.	94		16	
G 1	WO1-025G.	104			
G 1 1/4	WO1-032G.	120	65	19	1.5
G 1 1/2	WO1-040G.	130		20	1.6

G	Types	L	SW	X	Weight kg
G 1/4	WO1-008G.	71	36	9	0.3
G 3/8	WO1-010G.				
G 1/2	WO1-015G.	86	46	13	0.6
G 3/4	WO1-020G.	94		16	
G 1	WO1-025G.	104			
G 1 1/4	WO1-032G.	120	65	19	1.5
G 1 1/2	WO1-040G.	130		20	1.6

