OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

HONSBERG - UK & UKV SERIES FLOW INDICATOR

Flow display with float

UK-020GML0000
Flow meter 1/8", 0,04-0,5 Nl/min,air



- For liquids and air up to 6 bar
- Flow from 0.04 to 100 Nl/min. air (0.2 to 220 l/h water)
- With or without needle valve

PRODUCT DESCRIPTION

Model UK is a variable area type flow meter. It is available in two different versions, with or without needle valve. It has been developed to measure liquids and gases in various forms.

Special versions

• Special scales
• Connections in stainless steel
• Connections upwards and downwards (PVC)

TECHNICAL DATA

Accuracy	± 5% of full setpoint
Connection type	Internal thread, NPT 1/8 "
Flow range max	0.5 Nl/min
Flow range min	0.04 Nl/min
Function	Flow indicator, float body
Material of body	Acrylic
Material of connection	Brass
Material of seals	NBR
Material suspension body	Glass
Pressure drop	Approx. 0.1 bar at maximum flow
Pressure range max	6 bar

Temperature of media to	65 °C
Type of flow component	Flowmeter
Weight	0.13 kg



