**OEM Automatic Ltd**
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# HONSBERG - UK & UKV SERIES FLOW INDICATOR

Flow display with float

UKV-020GMW0006
Flow meter 1/8" w. valve, 0,5-6,0 l/h



- For liquids and air up to 6 bar
- Flow from 0.04 to 100 Nl/min. air (0.2 to 220 l/h water)
- With or without needle valve

### PRODUCT DESCRIPTION

Model UK is a variable area type flow meter. It is available in two different versions, with or without needle valve. It has been developed to measure liquids and gases in various forms.

## Special versions

• Special scales
• Connections in stainless steel
• Connections upwards and downwards (PVC)

# TECHNICAL DATA

| | |
|---|---|
| **Accuracy** | ± 5% of full setpoint |
| **Connection type** | Internal thread, NPT 1/8 " |
| **Flow max** | 0.1 l/min |
| **Flow range max** | 0.1 l/min |
| **Flow range min** | 0.008 l/min |
| **Function** | Flow indicator, swivel body, with needle valve |
| **Material of body** | Acrylic |
| **Material of connection** | Brass |
| **Material of seals** | NBR |
| **Material suspension body** | Glass |
| **Pressure drop** | Approx. 0.1 bar at maximum flow |

| | |
|---|---|
| **Pressure range max** | 6 bar |
| **Temperature of media to** | 65 °C |
| **Type of flow component** | Flowmeter |
| **Weight** | 0.13 kg |




