

HONSBERG - WO1 SERIES FLOW INDICATOR

Sight Glass

WO1-040GK
220l/min, G1 1/2, S/S

- G ¼ - 15l/min - G1½ - 220l/min
- Water , Oils
- DN-8-G ¼ - DN40-G1½
- Brass / Stainless Steel
- 16 Bar max




PRODUCT DESCRIPTION

TECHNICAL DATA

Connection type	G1 1/2 FEMALE
Flow range max	220 l/min
Flow range min	0 l/min
Material of connection	Stainless steel
Material of glass tube	Borosilicate glass
Material of seals	FKM
Material wipers	FKM
Media	WATER, OILS
Pressure range max	16 bar
Temperature of media from	-20 °C
Temperature of media to	100 °C
Weight	1.6 kg

G	Types	L	SW	X	Weight kg
G 1/4	WO1-008G.	71	36	9	0.3
G 3/8	WO1-010G.				
G 1/2	WO1-015G.	86	46	13	0.6
G 3/4	WO1-020G.	94		16	
G 1	WO1-025G.	104			
G 1 1/4	WO1-032G.	120	65	19	1.5
G 1 1/2	WO1-040G.	130		20	1.6



G	Types	L	SW	X	Weight kg
G 1/4	WO1-008G.	71	36	9	0.3
G 3/8	WO1-010G.				
G 1/2	WO1-015G.	86	46	13	0.6
G 3/4	WO1-020G.	94		16	
G 1	WO1-025G.	104			
G 1 1/4	WO1-032G.	120	65	19	1.5
G 1 1/2	WO1-040G.	130		20	1.6

