OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

DATASENSING VISION SENSOR DATAVS2 PRO

DATAVS2-08REPRO
Vision Sensor, 8mm lens, PRO, Red LED



- 360º pattern recognition / Controls for Bar code, Datamatrix
- Memory for up to 20 different inspections
- 3 outputs
- R232 interface


PRODUCT DESCRIPTION


DataVS2 is a series of Vision sensors for flexible solutions for machine applications.
The sensor is complete with optics, red LED lighting and electronics in a compact housing. The parameters in the sensor are set via PC through Ethernet communication. The software comes with the sensor and is developed to lead the user step by step through parameter setting. DataVS2 is available in 4 different versions with different control instruments.
The PRO model - handles the functions in the Advanced and ID models.
It manages 360º pattern recognition and also bar code, datamatrix and OCV. It also has 5 new instruments: 3 locators (Bar code, Datamatrix and 360º contour matching)
2 controls: 360º contour counter, 360º defect finder


TECHNICAL DATA

Digital interface	Ethernet 10/100 Mbs (4-pole M12 -connector)
Electrical connection	M12 4-pole D-coded, M12 8-pin connector
Frame rate	60
IP class	IP50
Lens material	ABS plastic
Material protection	Aluminium
Optics	8mm integrated lens
Output	3xPNP, RS232
Output current max	0.1 A
Power consumption max	0.1 A
Temperature operational max	50 °C
Temperature operational min	-10 °C
Voltage dc max	24 V


Voltage dc min	24 V
Voltage tolerance	10%




















The professional model includes in the same software all the functionalities already available on Advanced and Identification versions. Moreover it features 5 new software tools: 3 locators and 2 controls.

Locators	Functioning
Barcode	Finds a barcode in the Region Of Interest and re-locates all the other inspection controls accordingly. 
Datamatrix	Finds a datamatrix code in the Region Of Interest and re-locates all the other inspection controls accordingly. 
360° Contour Match	Finds a reference template in the Region Of Interest and re-locates all the other inspection controls accordingly. 

Controls	Functioning
360° Contour Counter	Counts how many times a reference contour is present in the Region Of Interest. 
360° Defect Finder	Detects even smallest defects on a part. 





M12 4-pole Ethernet



1 = white/orange = RX+
2 = white/green = TX+
3 = orange = RX-
4 = green = TX-

M12 8-pole (power supply and I/O)



OBJ and AOR models	ID and PRO models
1 = white = digital input 1	1 = white = RS232 RX
2 = brown = 24 Vdc	2 = brown = 24 Vdc
3 = green = configurable output	3 = green = configurable output
4 = yellow = output 1	4 = yellow = output 1
5 = grey = output 2	5 = grey = output 2
6 = pink = output 3	6 = pink = RS232 TX
7 = blue = GND	7 = blue = GND
8 = red = external trigger	8 = red = external trigger

