

OEM Automatic Ltd

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

BASLER ACE GIGE USB3.0 AND CAMERALINK CAMERAS

Ace Classic, Ace U and Ace L

ACA1600-20GC Ace GigE Camera, ICX274 1/1.8" CCD, 20fps, Colour, C-Mount

- Resolution: VGA to 20 MP and frame rate: up to 751 fps
- Supported by Pylon Suite software and open-source SDKs for easy image acquisition and fast application development
- CMOS Sensors with NIR function
- · Camera Link with PoCL
- · Very small housing





PRODUCT DESCRIPTION

Basler Ace Cameras, launched in 2009, are the smallest GigE camera on the market, also available with USB3.0 and Camera Link interface. With a small housing of only 29 x 29mm, the ace is suitable for a large range of vision applications, even where space is limited. There are over 130 models in the Ace range, split is Ace Classic, Ace U and Ace L. All featuring a range of resolutions from VGA to 20mp, speeds of up to 751 fps and sensors from a range of suppliers

Ace Classic model cameras have an excellent price/performance ratio and also feature a range of comprehensive sensors, including, CMOS from CMOSIS, e2V, ON Semiconductor (MT series) and CCD from Sony. The Ace classic range is available in GigE, USB3.0 and CameraLink.

Ace U cameras have the same compact footprint of the Ace Classic range (29 x 29mm), with the addition of unique PGI feature set from Basler and new CMOS sensors, in GigE and USB3.0 interfaces.

Ace L cameras feature the same additional firmware as Ace U but with high resolution 9 and 12mp Sony Pregius CMOS sensors, and optical formats above 1", to accommodate these larger sensors the Ace L is slightly larger with a footprint of 40mm x 30mm. With frame rates up to 40fps, the Ace L is available in GigE and USB3.0.

TECHNICAL DATA

ApprovalsCE, FCC, GenlCam, GigE Vision, RoHS, UL, EAC

| Digital outputs | 1 |
|-----------------------|----------------|
| Frame rate max | 20 fps |
| Height | 29 mm |
| Interface | GigE |
| IP class | IP30 |
| Length | 42 mm |
| Lens barrel | C-mount |
| Mono/color | Color |
| Operating temperature | 0°C 50°C |
| Pixel size | 4.4 x 4.4 |
| Power consumption | 2.9 W |
| Resolution | 2MP |
| Resolution max | 1624 x 1234 px |
| Sensor model | ICX274 |
| Sensor size | 1/1.8" |
| Sensor supplier | Sony |
| Sensor Type | CCD |
| Shutter type | Global |
| Weight | 90 g |
| Width | 29 mm |

