

## BASLER MED ACE GIGE AND USB3.0

Cameras for medical industry

ACA1920-40UMMED  
MED Ace USB3.0 Camera, IMX249, 1/1.2", CMOS,  
41fps, Mono



- Resolution: up to 20 MP and frame rate: up to 164 fps
- Supported by Pylon Suite software and open-source SDKs for easy image acquisition and fast application development
- In accordance with ISO 13485:2016
- Now with Dust Protection+
- Ideal for applications in medicine, medical tech and life sciences

### PRODUCT DESCRIPTION

Specifically designed for applications in medicine, medical technology and life science, the MED ace cameras are in accordance with ISO 13485:2016. Available in GigE and USB interface, with CMOS sensors from Sony Pregius series or PYTHON from ON Semiconductor. All models feature Basler MED Feature Sets which combine powerful hardware, firmware and software functions, to meet the high requirements of applications in Life and Medical Sciences market, additionally the MED Ace features low temporal dark noise up to  $2e^{-}$ .

Features on MED Ace:

- Up to 164 fps
- Up to 20 megapixel
- GigE and USB3.0 interfaces
- Pixel sizes up to  $5.86 \mu\text{m}$
- Sensor sizes up to 1.1"

### TECHNICAL DATA

<b>3612_Pixel size (<math>\mu\text{m}</math>)</b>	5.86 x 5.86
<b>Approvals</b>	CE, FCC, GenICam, RoHS, UL, EAC, USB3 Vision
<b>Digital inputs</b>	1
<b>Digital outputs</b>	1
<b>Frame rate max</b>	41 fps
<b>Height</b>	29 mm
<b>Interface</b>	USB 3.0
<b>IP class</b>	IP30
<b>Length</b>	29.3 mm
<b>Lens barrel</b>	C-mount
<b>Mono/color</b>	Mono
<b>Operating temperature</b>	0°C ... 50°C

<b>Power consumption</b>	2.5 W
<b>Resolution max</b>	1920 x 1200 px
<b>Sensor model</b>	IMX249
<b>Sensor size</b>	1/1.2"
<b>Sensor supplier</b>	Sony
<b>Sensor Type</b>	CMOS
<b>Shutter type</b>	Global
<b>Weight</b>	80 g
<b>Width</b>	29 mm