OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

SONY XCL-SG CAMERALINK CAMERAS

XCL-SG1240C
SONY CAMERALINK, 12.4MP, COLOUR, 20FPS

- 12.4MP or 5.1MP
- Pregius GSCMOS mono or colour sensor
- 20 fps or 154 fps
- Cameralink interface version 2.0



PRODUCT DESCRIPTION

With options of black and white or colour, these cameras combine the best of Sony technology in a convenient form factor which is optimised for use within both the Industrial Vision and non-manufacturing vision markets. They draw upon Sony's market leading Global Shutter CMOS sensor technology, combining the highly innovative, high resolution of Sony Pregius (12.4MP or 5.1MP) GSCMOS sensor with a rich heritage of complete camera technology, bringing the best combination of performance and quality from a brand you can trust.

Incorporating the very latest Pregius high sensitivity technology, these cameras provide an excellent balance between high resolution image and fast frame rate with the best visibility in challenging lighting environments.

TECHNICAL DATA

Camera model	Sony
Dimension (mm)	44(W) x 44(H) x 30(D)
Frame rate max	20 fps
Interface	Camera Link
Lens barrel	C Mount
Mono/color	Color
Power consumption	3.8 W
Resolution max	4,112 (H) x 3,008 (V)
Sensor size	1.1"
Sensor Type	CMOS
Shutter type	Global
User interface	CameraLink