

## MATROX IRIS GTX SMART CAMERA

GTX2000

Iris GTX smart camera, monochrome, 1920x1200,  
XGS2000, 4GB

- **High-Performance Processing:** Powered by an Intel Atom x6000 series processor, supporting fast, high-resolution image capture with deep learning capabilities for complex visual inspections
- **Rugged Industrial Design:** Compact, IP67-rated housing and robust M12 connectors make it suitable for demanding environments with dust, moisture, and extreme conditions
- **Integrated Autofocus and Lighting Control:** Features a Corning Varioptic auto-focus lens and LED lighting intensity control, allowing software-based adjustments to streamline setup and maintenance
- **Comprehensive Connectivity:** Equipped with Gigabit Ethernet, USB ports, VGA output, and real-time digital I/Os for seamless integration within automation systems
- **User-Friendly Vision Software:** Aurora Design Assistant provides a flowchart-based interface, enabling fast application development without coding for efficient machine vision deployment



### PRODUCT DESCRIPTION

### TECHNICAL DATA

Approvals	FCC Part 15 Class A, CE mark, EN55011 Class A, EN61326-1, ICES-003/NMB-003 Class A
Frame rate max	70 fps
Gain max	21.5 dB
IP class	IP67
Lens barrel	C-mount
Memory (RAM)	4 GB
Mono/color	Mono
Pixel size	3,2 x 3,2
Processor	Intel Atom x6211E
Resolution	2,3MP
Resolution max	1920x1200
Sensor model	XGS 2000

Sensor size	1/2.2"
Sensor supplier	ON Semiconductor
Shutter speed max	4.2 s
Shutter speed min	50 μs
Shutter type	Global
Storage	32 GB
Temperature operational max	45 °C
Temperature operational min	0 °C