0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

MATROX IRIS GTX SMART CAMERA

GTX2000C

Iris GTX smart camera, colour, 1920x1200, XGS2000, 4GB

₩.ZEBRA

- High-Performance Processing: Powered by an Intel Atom x6000 series processor, supporting fast, high-resolution image capture with deep learning capabilities for complex visual inspections
- Rugged Industrial Design: Compact, IP67-rated housing and robust M12 connectors make it suitable for demanding environments with dust, moisture, and extreme conditions
- Integrated Autofocus and Lighting Control: Features a Corning Varioptic auto-focus lens and LED lighting intensity control, allowing software-based adjustments to streamline setup and maintenance
- · Comprehensive Connectivity: Equipped with Gigabit Ethernet, USB ports, VGA output, and real-time digital I/Os for seamless integration within automation systems
- · User-Friendly Vision Software: Aurora Design Assistant provides a flowchart-based interface, enabling fast application development without coding for efficient machine vision deployment



PRODUCT DESCRIPTION

TECHNICAL DATA

| Approvals | FCC Part 15 Class A, CE mark, EN55011 Class A, EN61326-1, ICES-003/NMB-003 Class A |
|----------------|--|
| Frame rate max | 17 fps |
| Gain max | 21.5 dB |
| IP class | IP67 |
| Lens barrel | C-mount |
| Memory (RAM) | 4 GB |
| Mono/color | Color |
| Pixel size | 3,2 x 3,2 |
| Processor | Intel Atom x6211E |
| Resolution | 2,3MP |
| Resolution max | 1920x1200 |
| Sensor model | XGS 2000 |
| | |

| Sensor size | 1/2.2" |
|-----------------------------|------------------|
| Sensor supplier | ON Semiconductor |
| Shutter speed max | 4.2 s |
| Shutter speed min | 50 μs |
| Shutter type | Global |
| Storage | 32 GB |
| Temperature operational max | 45 °C |
| Temperature operational min | 0 °C |