

BASLER ACE GIGE USB3.0 AND CAMERALINK CAMERAS

Ace Classic, Ace U and Ace L

ACA2500-14GC/CS

Ace GigE Camera, MT9P031 1/2.5" CMOS, 14fps,
Colour, CS-Mount



- Resolution: VGA to 20 MP and frame rate: up to 751 fps
- Supported by Pylon Suite software and open-source SDKs for easy image acquisition and fast application development
- CMOS Sensors with NIR function
- Camera Link with PoCL
- Very small housing

PRODUCT DESCRIPTION

Basler Ace Cameras, launched in 2009, are the smallest GigE camera on the market, also available with USB3.0 and Camera Link interface. With a small housing of only 29 x 29mm, the ace is suitable for a large range of vision applications, even where space is limited. There are over 130 models in the Ace range, split is Ace Classic, Ace U and Ace L. All featuring a range of resolutions from VGA to 20mp, speeds of up to 751 fps and sensors from a range of suppliers

Ace Classic model cameras have an excellent price/performance ratio and also feature a range of comprehensive sensors, including, CMOS from CMOSIS, e2V, ON Semiconductor (MT series) and CCD from Sony. The Ace classic range is available in GigE, USB3.0 and CameraLink.

Ace U cameras have the same compact footprint of the Ace Classic range (29 x 29mm), with the addition of unique PGI feature set from Basler and new CMOS sensors, in GigE and USB3.0 interfaces.

Ace L cameras feature the same additional firmware as Ace U but with high resolution 9 and 12mp Sony Pregius CMOS sensors, and optical formats above 1", to accommodate these larger sensors the Ace L is slightly larger with a footprint of 40mm x 30mm. With frame rates up to 40fps, the Ace L is available in GigE and USB3.0.

TECHNICAL DATA

Approvals

CE, FCC, GenICam, GigE Vision, RoHS, UL, EAC

Digital inputs

1

Digital outputs	1
Frame rate max	14 fps
Height	29 mm
Interface	GigE
IP class	IP30
Length	42 mm
Lens barrel	CS-mount
Mono/color	Color
Operating temperature	0°C ... 50°C
Pixel size	2.2 x 2.2
Power consumption	2.2 W
Resolution	5MP
Resolution max	2590 x 1942 px
Sensor model	MT9P031
Sensor size	1/2.5"
Sensor supplier	ON Semiconductor
Sensor Type	CMOS
Shutter type	Rolling
Weight	90 g
Width	29 mm

