

## **OEM Automatic Ltd**

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

## BASLER ACE GIGE USB3.0 AND CAMERALINK CAMERAS

Ace Classic, Ace U and Ace L

ACA640-90UC/CS Ace USB3.0 Camera, ICX424 1/3" CCD, 90fps, Colour, CS-Mount

- ace
- Resolution: VGA to 20 MP and frame rate: up to 751 fps
- Supported by Pylon Suite software and open-source SDKs for easy image acquisition and fast application development
- CMOS Sensors with NIR function
- Camera Link with PoCL
- · Very small housing

## PRODUCT DESCRIPTION

Basler Ace Cameras, launched in 2009, are the smallest GigE camera on the market, also available with USB3.0 and Camera Link interface. With a small housing of only 29 x 29mm, the ace is suitable for a large range of vision applications, even where space is limited. There are over 130 models in the Ace range, split is Ace Classic, Ace U and Ace L. All featuring a range of resolutions from VGA to 20mp, speeds of up to 751 fps and sensors from a range of suppliers

Ace Classic model cameras have an excellent price/performance ratio and also feature a range of comprehensive sensors, including, CMOS from CMOSIS, e2V, ON Semiconductor (MT series) and CCD from Sony. The Ace classic range is available in GigE, USB3.0 and CameraLink.

Ace U cameras have the same compact footprint of the Ace Classic range (29 x 29mm), with the addition of unique PGI feature set from Basler and new CMOS sensors, in GigE and USB3.0 interfaces.

Ace L cameras feature the same additional firmware as Ace U but with high resolution 9 and 12mp Sony Pregius CMOS sensors, and optical formats above 1", to accommodate these larger sensors the Ace L is slightly larger with a footprint of 40mm x 30mm. With frame rates up to 40fps, the Ace L is available in GigE and USB3.0.

## **TECHNICAL DATA**

**Approvals** CE, FCC, GenlCam, RoHS, UL, EAC, USB3 Vision



Digital outputs	1
Frame rate max	90 fps
Height	29 mm
Interface	USB3.0
IP class	IP30
Length	29.3 mm
Lens barrel	CS-mount
Mono/color	Color
Operating temperature	0°C 50°C
Pixel size	7.4 x 7.4
Power consumption	2.7 W
Resolution	VGA
Resolution max	658 x 492 px
Sensor model	ICX424
Sensor size	1/3"
Sensor supplier	Sony
Sensor Type	CCD
Shutter type	Global
Weight	80 g
Width	29 mm

