**OEM Automatic Ltd**
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# BASLER ACE GIGE USB3.0 AND CAMERALINK CAMERAS

Ace Classic, Ace U and Ace L

ACA2440-20GM
Ace U GigE Camera, IMX264 2/3" CMOS, 23fps, Mono, C-Mount




- Resolution: VGA to 20 MP and frame rate: up to 751 fps
- Supported by Pylon Suite software and open-source SDKs for easy image acquisition and fast application development
- CMOS Sensors with NIR function
- Camera Link with PoCL
- Very small housing

**PRODUCT DESCRIPTION**

Basler Ace Cameras, launched in 2009, are the smallest GigE camera on the market, also available with USB3.0 and Camera Link interface. With a small housing of only 29 x 29mm, the ace is suitable for a large range of vision applications, even where space is limited. There are over 130 models in the Ace range, split is Ace Classic, Ace U and Ace L. All featuring a range of resolutions from VGA to 20mp, speeds of up to 751 fps and sensors from a range of suppliers

Ace Classic model cameras have an excellent price/performance ratio and also feature a range of comprehensive sensors, including, CMOS from CMOSIS, e2V, ON Semiconductor (MT series) and CCD from Sony. The Ace classic range is available in GigE, USB3.0 and CameraLink.

Ace U cameras have the same compact footprint of the Ace Classic range (29 x 29mm), with the addition of unique PGI feature set from Basler and new CMOS sensors, in GigE and USB3.0 interfaces.

Ace L cameras feature the same additional firmware as Ace U but with high resolution 9 and 12mp Sony Pregius CMOS sensors, and optical formats above 1”, to accommodate these larger sensors the Ace L is slightly larger with a footprint of 40mm x 30mm. With frame rates up to 40fps, the Ace L is available in GigE and USB3.0.

# TECHNICAL DATA

| | |
|---|---|
| **Sensor model** | IMX264 |
| **Resolution max** | 2448 x 2048 px |

| | |
|---|---|
| **Frame rate max** | 23 fps |
| **Mono/color** | Mono |
| **Shutter type** | Global |
| **Interface** | GigE |
| **3612_Pixel size (µm)** | 3.45 x 3.45 |
| **Sensor size** | 2/3" |
| **Digital outputs** | 1 |
| **Digital inputs** | 1 |
| **Approvals** | CE, FCC, GenICam, GigE Vision, RoHS, UL, EAC |
| **IP class** | IP30 |
| **Sensor supplier** | Sony |
| **Sensor Type** | CMOS |
| **Lens barrel** | C-mount |
| **Weight** | 90 g |
| **Length** | 42 mm |
| **Width** | 29 mm |
| **Height** | 29 mm |
| **Power consumption** | 2.7 W |
| **Operating temperature** | 0°C … 50°C |

