**OEM Automatic Ltd**
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# BASLER RACER 2S LINE SCAN CAMERAS

Small Form Factor Line Cameras

R2L2048-62CC
Basler Racer 2- GL3504 Sensor, CoaXPress (CXP-12) Interface, 2k Resolution, 62kHz Line Rate, Colour




- 2 k & 4 k resolution and up to 172 kHz Line Rate
- Supported by Pylon software suite for easy image acquisition
- Colour & Monochrome cameras
- GigE, 5GigE and CXP-12 interfaces
- 29 x 29 mm form factor

### PRODUCT DESCRIPTION

Basler's Racer 2S line scan cameras are high-performance imaging solutions designed for industrial environments requiring precise and high-speed inspection. Built with the CoaXPress 2.0 interface, these cameras deliver data rates of up to 12.5 Gbps per channel, ensuring fast image transmission even at high resolutions. The Racer 2S series features sensors with resolutions ranging from 2K to 16K and supports line rates up to 140 kHz. Equipped with CMOS sensor technology, these cameras offer excellent image quality, low noise levels, and high dynamic range—ideal for applications that demand fine detail and rapid throughput.
These cameras are particularly well-suited for practical applications such as web inspection in printing, textiles, and paper production, as well as semiconductor inspection and sorting processes in logistics and food industries. Their compact housing and standard lens mounts make integration straightforward, even in space-constrained setups. Thanks to the CoaXPress interface, users benefit from long cable lengths and reliable, high-speed data transfer, making Racer 2S cameras an excellent choice for scalable, high-performance line scan systems in modern industrial automation environments.

# TECHNICAL DATA

| | |
|---|---|
| **Mono/color** | Color |
| **Resolution max** | 2048 x 1 px |
| **Line speed max** | 62 kHz |
| **3612_Pixel size (µm)** | 7 x 7 |
| **Sensor model** | GL3504 |
| **IP class** | IP30 |
| **Approvals** | CE, EAC, FCC, GenICam, RoHS, UL |

| | |
|---|---|
| **Sensor size** | 14.34 mm |
| **Sensor supplier** | Gpixel |
| **Sensor Type** | CMOS |
| **Shutter type** | Global |
| **Weight** | 100 g |
| **Digital inputs** | 3 |

| | |
|---|---|
| **Digital outputs** | 2 |
| **Length** | 62.2 mm |
| **Width** | 29 mm |
| **Height** | 29 mm |
| **Lens Barrel** | C-Mount |
| **Operating temperature** | -10°C ... 60°C |