

ACE 2X VISSWIR

Advanced Cameras with SWIR Technology

a2A2048-173cmSWIR
Basler ACE 2 CoaXPress Interface, 173 FPS, IMX993
Sensor, 1/1.8" Sensor Format, 3.1 MP Resolution



- VGA and 1.3 Megapixel
- Up to 240 fps
- Available models for both USB 3.0 and GigE
- Rugged M8 connector
- Compact format

PRODUCT DESCRIPTION

The Basler ace 2X visSWIR cameras are high-performance industrial cameras engineered to capture both visible and short-wave infrared (SWIR) spectra, making them highly versatile for demanding imaging applications. These cameras utilise Sony's innovative SenSWIR InGaAs sensors, offering high quantum efficiency across a broad spectral range from approximately 400 nm to 1700 nm. With resolutions typically up to 1.3 megapixels and frame rates exceeding 100 frames per second, the ace 2X visSWIR series supports GigE Vision and USB 3.0 interfaces, ensuring fast data transfer and seamless integration with standard machine vision systems. Key technical features include Basler's PGI image optimisation, precision time protocol (PTP) for synchronisation, and a robust hardware design suitable for industrial environments.

In practical applications, the ace 2X visSWIR cameras are particularly useful in industries where visibility into both the visible and SWIR spectra is critical. These include semiconductor inspection, agricultural sorting, food quality analysis, and pharmaceutical verification, where material differentiation beyond the visible range enhances process control and quality assurance. The dual-spectrum capability enables tasks like detecting moisture content, inspecting silicon wafers, or identifying contaminants in food production. Their compact design and compatibility with Basler's powerful pylon Camera Software Suite also make them ideal for system integrators building advanced vision systems with complex spectral analysis needs.

TECHNICAL DATA

Approvals	CE, CoaXPress 2.0, EAC, FCC, GenICam, RoHS, UKCA
Digital inputs	1
Exposure control	hardware trigger and programmable via the camera API
Frame rate max	173 fps
Height	29 mm
Interface	CoaXPress
IP class	IP30
Length	42.8 mm
Mono/color	Mono
Operating temperature	0 °C - 50 °C
Pixel size	3.45 µm × 3.45 µm
Resolution	3.1 MP
Resolution max	2048 px × 1536 px

Sensor model	IMX993
Sensor size	1/1.8"
Shutter type	Global
Synchronization	free-run, hardware trigger and software trigger
Wavelength	Visible + SWIR
Weight	90 g
Width	29 mm

