

IDEM - IDEMAG - CPR SWITCH

113016

CPR QC M12 8way '1NC 1NO'

- Polyester housing
- Narrow housing 20 mm
- Switching range 12 mm
- Loads up to 2 A
- No dedicated controller



PRODUCT DESCRIPTION

The IDEMAG - CPR switch is a magnetic switch made of high tolerance polyester, which is ideal for all industrial applications. It allows to switch currents, depending on the model, to 1 A or 2 A. The slim switch housing - 20 mm gives the possibility of mounting in applications with a limited space for mounting. The switch is resistant to pressure washing.

TECHNICAL DATA

Annual usage	8 cycles per hour/24hours per day/365 days
Approvals	ISO 14119, EN60947-5-1, EN60204-1, ISO 13849-1, EN62061, UL 508
Cable length	0.25 m
Cable type	PVC 6 or 8 core 6mm OD conductors 0.25 ²
Coding	Not coded
Conductor size	0.25 mm ²
Contact rating max	250Vac 2.0A
Contacts	1NC 1NO
Housing material	Polyester
Integrated LED indication	No
IP class	IP69K, IP67
Mechanical reliability B10d	3.3 x 10 ⁶ operations at 100mA load

Mounting	2 x M4
MTTFd	470 years
Operating temperature	-25..80°C
PFHd	2.52 x 10 ⁻⁸
PL	e acc. ISO13849-1
Recommended mounting gap	5 mm
SIL	3 acc. EN62061
Switching current min	10Vdc 1mA
Switching distance	Sao 10mm close, Sar 22mm open
Switching frequency max	1.0Hz maximum

