OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

CROSS CONNECTORS FOR PRK, PSL, PRKD, PPVK, PTKS RANGE

Push In Terminal Cross Connectors - PQI

27143.9
PQI 4/3, 3 way Cross connector for PRK/PSL 4mm² - Red



- Fully rated for the matching terminal
- Plug in for fast and easy connection
- Pins can be removed for jumping terminals

PRODUCT DESCRIPTION

The PQI pluggable cross-connectors helps you to save time while distributing potentials over terminal blocks of similar or different cross-section ranges.
The pluggable design of the PQI offers the advantage that it can carry the full rated current even while operating at the fully rated voltage.
The PQI is insulated to protect against accidental touch and is available in the cross-section range from 1.5 mm² to 10 mm² in 2-, 3-, 4-, 10- and 20-pole versions and 2 way for 16mm² terminals.
Standard colour is Red, but Blue & Black are also available.

TECHNICAL DATA

GENERAL DATA

Colour	Red
Mounting	Plug in

DIMENSIONS

Length	4 mm
Width	16.2 mm
Height	19.4 mm
Pitch	6.1 mm

CONNECTION DATA

Number of poles	3

MATERIALS

Insulation material	Polyamide 6.6
Flammability class	UL94-V0

Operating temperature from	-40 °C
Operating temperature to	120 °C

ADDITIONAL DATA

Tariff code	85389099
Country of origin	DE
Weight	2.78 g
Pack size	50

Number of poles	3








