OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

DIN RAIL & BRACKETS

TS, TST, TWST

2414.0
TSTW/M5, Bracket, 48mm, M5



- Angled mounting brackets
- TS35, TS15 & G-rail
- Galvanised, passivated steel or aluminium versions
- Slotted or solid
- Custom sizes

PRODUCT DESCRIPTION

The Conta-Clip din rail conforms to the European Standard EN 60715 and are available with various slot sizes or as solid rail.

Most or the range are available in galvanised steel or with the zinc/chromate plating. Aluminium rails can be offered but are subject to minimum order quantities. We also offer protective caps to reduce the need for deburring and protection against the sharp-edged ends on the rail

A selection of galvanised passivated steel angled brackets is also available to stand of the rail from the back plates. These have either M5 or M6 threaded hole as standard.

OEM can offer Custom pre-cut sizes to suit your application and reduce assembly time. Please contact panel@oem.co.uk for pricing on pre-cut rail or fully assembled terminal assemblies.

TECHNICAL DATA

GENERAL DATA

Colour	Natural

DIMENSIONS

Height	48 mm

MATERIALS

Material	Galvanized, thick-film passivated, Steel

Thread size	M5