

OEM Automatic Ltd

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

CONTACLIP

DIN RAIL & BRACKETS

TS, TST, TWST

4562.0 TS 35 x 7.5mm, Solid Galvanised

- · Angled mounting brackets
- TS35, TS15 & G-rail
- Galvanised, passivated steel or aluminium versions
- · Slotted or solid
- · Custom sizes



PRODUCT DESCRIPTION

The Conta-Clip din rail conforms to the European Standard EN 60715 and are available with various slot sizes or as solid rail.

Most or the range are available in galvanised steel or with the zinc/chromate plating. Aluminium rails can be offered but are subject to minimum order quantities. We also offer protective caps to reduce the need for deburring and protection against the sharp-edged ends on the rail

A selection of galvanised passivated steel angled brackets is also available to stand of the rail from the back plates. These have either M5 or M6 threaded hole as standard.

OEM can offer Custom pre-cut sizes to suit your application and reduce assembly time. Please contact panel@oem.co.uk for pricing on pre-cut rail or fully assembled terminal assemblies.

TECHNICAL DATA

GENERAL DATA

Country of origin

Weight

GENERAL DATA		
Colour	Natural	
DIMENSIONS		
Length	2000 mm	
Width	35 mm	
Height	7.5 mm	
MATERIALS		
Material	Steel	
ADDITIONAL DATA		
Tariff code	72166110	

EEC

347 g

Pack size	40
VDE test standard	Entspricht DIN VDE 0611 Teil 3
Contact surface	Galvanized
DIN approvals	DIN EN 60715