

## DIRECT MOUNT SCREW TERMINALS

BAK, RD-D

1355.2

BAK 2.5/5 b.B. Beige, 2.5mm<sup>2</sup>, 5-pole Direct mount  
compact with tags both sides

- Compact 2.5mm -10mm<sup>2</sup> versions snap together
- Pre-labeled versions
- RK-D 50mm -240mm<sup>2</sup> Direct mount
- External cross connectors



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### GENERAL DATA

Rated wire cross section	2.5 mm <sup>2</sup>
Colour	Beige
Rated voltage IEC	400 V
Rated current IEC	24 A
Mounting	Direct mount
Rated impulse voltage	6 kV
Overvoltage category	III
Contamination degree	3
Approvals	UL, cUL, KEMA KUR, EAC
Additional information	with marking on both sides

#### DIMENSIONS

Length	44.9 mm
Height	23 mm
Distance to hole centres	37.8 mm

#### CONNECTION DATA

Connections	12
-------------	----

Number of levels	1
Plug gauge acc. EN 60 947-1	A3
Cross section single wire from	0.2 mm <sup>2</sup>
Cross section single wire to	4 mm <sup>2</sup>
Cross section stranded wire from	0.2 mm <sup>2</sup>
Cross section stranded wire to	4 mm <sup>2</sup>
Cross section stranded with ferrule from	0.2 mm <sup>2</sup>
Cross section stranded with ferrule to	2.5 mm <sup>2</sup>
Rated wire cross section from (AWG)	22
Rated wire cross section to (AWG)	12
Stripping length	7 mm
Screw size	M 2,5
Screw type	Slotted
Torque min	0.4
Torque max	0.8

## MATERIALS

Insulation material	Polyamide 6.6
Flammability class	UL94-V2
Operating temperature from	-40 °C
Operating temperature to	105 °C

## APPROVALS

Rated voltage UL	300 V
Rated current UL	20 A
UL test standard	UL 1059
Rated voltage cUL	300 V
Rated current cUL	20 A
cUL test standard	C22.2 No 158
EAC test standard	TR ZU 004/2011
KEMA KEUR test standard	EN 60947-7-1:2009

## ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	25 g

