

## CROSS CONNECTORS FOR SRK, SSL & SRKD RANGE

SQI, SQ

17204.5  
SQI 2.5/5 BU - 5 Way Cross Connector for  
SRK/SSL/SRKD 2.5/2A

- For SRK 2.5-120mm<sup>2</sup>
- Insulated plug in up to 35mm<sup>2</sup>
- Fully rated
- Can be cut down with insulated cap. No partition required
- Screw in 50-120mm<sup>2</sup>



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### GENERAL DATA

|                               |                     |
|-------------------------------|---------------------|
| Rated wire cross section      | 2.5 mm <sup>2</sup> |
| Colour                        | Blue                |
| Max voltage with partition    | 1000 V              |
| Max voltage without partition | 1000 V              |
| Rated current IEC             | 24 A                |
| Load current max              | 32 A                |
| Mounting                      | Push in             |
| Contamination degree          | 3                   |

#### DIMENSIONS

|        |         |
|--------|---------|
| Length | 4 mm    |
| Width  | 25.2 mm |
| Pitch  | 5 mm    |

#### CONNECTION DATA

|                 |   |
|-----------------|---|
| Number of poles | 5 |
|-----------------|---|

MATERIALS

|                            |               |
|----------------------------|---------------|
| Material                   | Bronze        |
| Insulation material        | Polyamide 6.6 |
| Flammability class         | UL94-V2       |
| Operating temperature from | -40 °C        |
| Operating temperature to   | 105 °C        |

ADDITIONAL DATA

|                   |          |
|-------------------|----------|
| Tariff code       | 85369010 |
| Country of origin | DE       |
| Weight            | 3 g      |
| Pack size         | 20       |