

**CROSS CONNECTORS FOR SRK, SSL & SRKD RANGE**

SQI, SQ

17211.5  
SQI 4/2 BU - 2 Way Cross Connector for  
SRK/SSL/SRKD 4/2A

- For SRK 2.5-120mm<sup>2</sup>
- Insulated plug in up to 35mm<sup>2</sup>
- Fully rated
- Can be cut down with insulated cap. No partition required
- Screw in 50-120mm<sup>2</sup>

**PRODUCT DESCRIPTION****TECHNICAL DATA****GENERAL DATA**

Rated wire cross section	4 mm <sup>2</sup>
Colour	Blue
Max voltage with partition	1000 V
Max voltage without partition	1000 V
Rated current IEC	32 A
Load current max	41 A
Mounting	Push in
Contamination degree	3

**DIMENSIONS**

Length	4 mm
Width	11.3 mm
Pitch	6 mm

**CONNECTION DATA**

Number of poles	2
-----------------	---

## MATERIALS

<b>Material</b>	Bronze
<b>Insulation material</b>	Polyamide 6.6
<b>Flammability class</b>	UL94-V2
<b>Operating temperature from</b>	-40 °C
<b>Operating temperature to</b>	105 °C

## ADDITIONAL DATA

<b>Tariff code</b>	85369010
<b>Country of origin</b>	DE
<b>Weight</b>	1.3 g
<b>Pack size</b>	50