

CROSS CONNECTORS FOR SRK, SSL & SRKD RANGE

SQI, SQ

17213.4
SQI 4/3 BK - 3 Way Cross Connector for
SRK/SSL/SRKD 4/2A

- For SRK 2.5-120mm²
- Insulated plug in up to 35mm²
- Fully rated
- Can be cut down with insulated cap. No partition required
- Screw in 50-120mm²



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

| | |
|-------------------------------|-------------------|
| Rated wire cross section | 4 mm ² |
| Colour | Black |
| Max voltage with partition | 1000 V |
| Max voltage without partition | 1000 V |
| Rated current IEC | 32 A |
| Load current max | 41 A |
| Mounting | Push in |
| Contamination degree | 3 |

DIMENSIONS

| | |
|--------|---------|
| Length | 4 mm |
| Width | 23.5 mm |
| Pitch | 6 mm |

CONNECTION DATA

| | |
|-----------------|---|
| Number of poles | 4 |
|-----------------|---|

MATERIALS

| | |
|----------------------------|---------------|
| Material | Bronze |
| Insulation material | Polyamide 6.6 |
| Flammability class | UL94-V2 |
| Operating temperature from | -40 °C |
| Operating temperature to | 105 °C |

ADDITIONAL DATA

| | |
|-------------------|----------|
| Tariff code | 85369010 |
| Country of origin | DE |
| Weight | 2.7 g |
| Pack size | 20 |