

## CROSS CONNECTORS FOR SRK, SSL & SRKD RANGE

SQI, SQ

17220.4

SQI 4/30 BK - 30 Way Cross Connector for SRK/SSL/SRKD 4/2A

- For SRK 2.5-120mm<sup>2</sup>
- Insulated plug in up to 35mm<sup>2</sup>
- Fully rated
- Can be cut down with insulated cap. No partition required
- Screw in 50-120mm<sup>2</sup>



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### GENERAL DATA

Rated wire cross section	4 mm <sup>2</sup>
Colour	Black
Max voltage with partition	1000 V
Max voltage without partition	1000 V
Rated current IEC	32 A
Load current max	41 A
Mounting	Push in
Contamination degree	3

#### DIMENSIONS

Length	4.2 mm
Width	181.1 mm
Pitch	6 mm

#### CONNECTION DATA

Number of poles	30
-----------------	----

**MATERIALS**

Material	Bronze
Insulation material	Polyamide 6.6
Flammability class	UL94-V2
Operating temperature from	-40 °C
Operating temperature to	105 °C

**ADDITIONAL DATA**

Tariff code	85369010
Country of origin	DE
Weight	21 g
Pack size	5