

## CROSS CONNECTORS FOR SRK, SSL & SRKD RANGE

SQI, SQ

17239.4

SQI 10/10 BK - 10 Way Cross Connector for SRK/SSL/SRKD 10/2A

- For SRK 2.5-120mm<sup>2</sup>
- Insulated plug in up to 35mm<sup>2</sup>
- Fully rated
- Can be cut down with insulated cap. No partition required
- Screw in 50-120mm<sup>2</sup>



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### GENERAL DATA

Rated wire cross section	10 mm <sup>2</sup>
Colour	Black
Max voltage with partition	1000 V
Max voltage without partition	1000 V
Rated current IEC	57 A
Load current max	76 A
Mounting	Push in
Contamination degree	3

#### DIMENSIONS

Length	4 mm
Width	98.3 mm
Pitch	10 mm

#### CONNECTION DATA

Number of poles	10
-----------------	----

MATERIALS

Material	Copper alloy
Insulation material	Polyamide 6.6
Flammability class	UL94-V2
Operating temperature from	-40 °C
Operating temperature to	105 °C

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	13.5 g
Pack size	5