OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

CROSS CONNECTORS FOR ZRK/ZST TENSION SPRING RANGE

Tension Spring Terminal Cross Connectors - ZQI

3715.4
ZQI 2.5/7 BK, 7 Way Cross Connector for 2.5mm
ZSRK/ZRK/ZSL/ZST/ZIZA - Black



- For ZRK, ZSRK, ZST and ZINI/ZAKTO
- Insulated plug in
- Can be cut down

PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Rated wire cross section	2.5 mm²
Colour	Black
Max voltage with partition	800 V
Max voltage without partition	800 V
Rated current IEC	24 A
Mounting	Push in
Contamination degree	3

DIMENSIONS

Length	4.5 mm
Width	34.6 mm
Pitch	5 mm

CONNECTION DATA

Number of poles	7

MATERIALS

Material	Copper alloy
Insulation material	Polyamide 6.6
Flammability class	UL94-V2
Operating temperature from	-40 °C
Operating temperature to	105 °C

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	4 g
Pack size	20