

## CROSS CONNECTORS FOR SRK, SSL & SRKD RANGE

SQI, SQ

17223.8

SQI 6/4 YE - 4 Way Cross Connector for SRK/SSL 6/2A

- For SRK 2.5-120mm<sup>2</sup>
- Insulated plug in up to 35mm<sup>2</sup>
- Fully rated
- Can be cut down with insulated cap. No partition required
- Screw in 50-120mm<sup>2</sup>



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### GENERAL DATA

Rated wire cross section	6 mm <sup>2</sup>
Colour	Yellow
Max voltage with partition	1000 V
Max voltage without partition	1000 V
Rated current IEC	41 A
Load current max	57 A
Mounting	Push in
Contamination degree	3

#### DIMENSIONS

Length	4 mm
Width	30.5 mm
Pitch	8 mm

#### CONNECTION DATA

Number of poles	4
-----------------	---

**MATERIALS**

Material	Copper alloy
Insulation material	Polyamide 6.6
Flammability class	UL94-V2
Operating temperature from	-40 °C
Operating temperature to	105 °C

**ADDITIONAL DATA**

Tariff code	85369010
Country of origin	DE
Weight	4.4 g
Pack size	20