
OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

CROSS CONNECTORS FOR RK, IK, DLI & SK RANGE

Q, QI

2164.0
Q 2 - 2 pole cross connector for RK 35, (RK 35N Old Type)



- Screw in
- Insulated versions
- Can be cut down

PRODUCT DESCRIPTION

The Q/QI screwable cross-connector system allows you to quickly link terminal blocls of the same size.

The QI range is touch-safe and are generally available in 2, 3, 4 or 10 poles, some variants have up to 98 poles, which can be cut down as required.

With both ranges it is possible to 'skip' over terminals by breaking out the conductor (QI) or removing the screw and sleeve (Q).

TECHNICAL DATA

GENERAL DATA

Rated wire cross section	35 mm²
Max voltage with partition	800 V
Max voltage without partition	400 V
Rated current IEC	65 A
Mounting	Screw in
Contamination degree	3
Additional information	for RK 35…

DIMENSIONS

Length	8 mm
Width	25 mm
Distance to hole centres	16 mm

Pitch	16 mm
Hole diameter	4.6 mm

CONNECTION DATA

Number of poles	2
Screw size	M 4
Screw type	Slotted
Torque min	1.2
Torque max	2

MATERIALS

Material	Brass

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	18.3 g
Pack size	20