


## CROSS CONNECTORS FOR RK, IK, DLI & SK RANGE

Q, QI

2167.0

Q 10 - 10 pole cross connector for RK 35, (RK 35N Old Type)

- Screw in
- Insulated versions
- Can be cut down



### PRODUCT DESCRIPTION

The Q/QI screwable cross-connector system allows you to quickly link terminal blocks of the same size.

The QI range is touch-safe and are generally available in 2, 3, 4 or 10 poles, some variants have up to 98 poles, which can be cut down as required.

With both ranges it is possible to 'skip' over terminals by breaking out the conductor (QI) or removing the screw and sleeve (Q).

## TECHNICAL DATA

### GENERAL DATA

Rated wire cross section	35 mm <sup>2</sup>
Max voltage with partition	800 V
Max voltage without partition	400 V
Rated current IEC	65 A
Mounting	Screw in
Contamination degree	3
Additional information	for RK 35...

### DIMENSIONS

Length	8 mm
Width	153 mm
Distance to hole centres	16 mm

Pitch	16 mm
Hole diameter	4.6 mm

CONNECTION DATA

Number of poles	10
Screw size	M 4
Screw type	Slotted
Torque min	1.2
Torque max	2

MATERIALS

Material	Brass
----------	-------

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	97.6 g
Pack size	10