OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

EXTERNAL LINK CROSS CONNECTORS

AQI External Terminal Link Bars

2766.2
AQI 3/95 - 3 pole External Cross connector for RK95



- Insulated for protection
- Reliable & secure fixing
- Easy Installation

PRODUCT DESCRIPTION

External cross connection links makes it possible to connect potentials of terminals where there is no option of a central cross connection channel.

These links are quicker, easier and a more reliable way of linking than using wire links with ferrules.

When using the external, the rated cross section of wire is reduced to the next smallest size.

TECHNICAL DATA

GENERAL DATA

Colour	Yellow
Max voltage with partition	1000 V
Max voltage without partition	1000 V
Rated current IEC	232 A
Mounting	Push in
Contamination degree	3
Additional information	for RK 95

DIMENSIONS

Width	70.44 mm
Pitch	25 mm

CONNECTION DATA

Number of poles	3

MATERIALS

Material	Copper

Insulation material	Polyamide 6.6
Flammability class	UL94-V2
Operating temperature from	-40 °C
Operating temperature to	105 °C

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	144 g
Pack size	5