

EXTERNAL LINK CROSS CONNECTORS

AQI External Links

2770.2

AQI 3/240 - 3 pole External Cross connector for RK240

- Insulated for protection
- Reliable & secure fixing



PRODUCT DESCRIPTION

External cross connection links makes it possible to connect potentials of terminals where there is no option of a central cross connection channel.

These links are quicker, easier and a more reliable way of linking than using wire links with ferrules.

When using the external, the rated cross section of wire is reduced to the next smallest size.

TECHNICAL DATA

GENERAL DATA

| | |
|-------------------------------|------------|
| Colour | Yellow |
| Max voltage with partition | 1000 V |
| Max voltage without partition | 1000 V |
| Rated current IEC | 380 A |
| Mounting | Push in |
| Contamination degree | 3 |
| Additional information | for RK 240 |

DIMENSIONS

| | |
|-------|-----------|
| Width | 103.12 mm |
| Pitch | 36 mm |

CONNECTION DATA

| | |
|-----------------|---|
| Number of poles | 3 |
|-----------------|---|

MATERIALS

| | |
|----------------------------|---------------|
| Material | Copper |
| Insulation material | Polyamide 6.6 |
| Flammability class | UL94-V2 |
| Operating temperature from | -40 °C |
| Operating temperature to | 105 °C |

ADDITIONAL DATA

| | |
|-------------------|----------|
| Tariff code | 85369010 |
| Country of origin | DE |
| Weight | 317.84 g |
| Pack size | 5 |