

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk


CONTACLIP

EXTERNAL LINK CROSS CONNECTORS

AQI External Links

2069.0 AQI 4/8/11 - 4 pole External Cross connector for STK1/STK2/STKD1/BKA10

- Insulated for protection
- Reliable & secure fixing



PRODUCT DESCRIPTION

External cross connection links makes it possible to connect potentials of terminals where there is no option of a central cross connection channel.

These links are quicker, easier and a more reliable way of linking than using wire links with ferrules.

When using the external, the rated cross section of wire is reduced to the next smallest size.

TECHNICAL DATA

GENERAL DATA

Colour	Yellow
Rated current IEC	27 A
Mounting	Push in
Contamination degree	3
Additional information	for BKA 10 STK 1 STK 2 STKD 1

DIMENSIONS

Width	32.3 mm
Pitch	8 mm

CONNECTION DATA

Number of poles	4		
-----------------	---	--	--

MATERIALS

Material	Copper
Insulation material	Polyamide 6.6

Flammability class	UL94-V2
Operating temperature from	-40 °C
Operating temperature to	105 °C

ADDITIONAL DATA

Tariff code	85389099
Country of origin	DE
Weight	1.78 g
Pack size	50